



INSTALLATION INSTRUCTIONS

Part Number: VF2061

This filter fits: SEE CATALOG FOR CURRENT APPLICATIONS

* FREE K&N® decal To register your warranty, please see us online at knfilters.com/register. FREE K&N® decal *

K&N® Cabin Air Filters replace your vehicle's stock cabin filter with a reusable design that cleans and freshens incoming air. They are electrostatically charged to grab and hold dust particles. K&N® cabin air filters help control odors while they help capture most mold, mildew, fungus, spores, bacteria and germs. When they get dirty they can be cleaned and reused and best of all, they come with a 10 year/Million mile limited warranty.

If you need any assistance please call 1-800-858-3333 to speak with a representative in our Customer Service Center before returning the product.

When applicable, refer to owner's manual for manufacturers installation/removal instructions. The following are helpful steps when replacing/servicing cabin air filter with K&N® cabin air filter.

1. Open the glove box and locate the shock mount on the right side. Fig. 1
2. Remove the shock eyelet from the mount. Fig 2
3. Remove the bump stops on the sides of the glove box by twisting them counter-clockwise. Figs. 3 & 4
4. Open the cabin filter cover door and remove the dirty filter. Clean out any dirt or debris from the housing. Figs. 5 & 6
5. Install the new K&N® Cabin Filter with the K&N® logo facing out. Fig. 7 & 8
6. Reverse steps 2-4 to complete the cabin filter installation. With the cabin filter installed, clean an area near the filter door and apply the K&N® Stop Decal. The decal will help notify others that this is a re-usable cabin filter.



Fig. 1



Fig. 2



Fig. 3



Fig. 4



Fig. 5



Fig. 6



Fig. 7



Fig. 8

Please visit our website knfilters.com for a complete listing of other K&N® products for your vehicle, such as oil filters, air filters, and intake kits. We recommend refreshing your K&N® Cabin Air Filter every 12 months, or 12,000 miles. Use K&N® Refresher kit pt.# 99-6000 which includes the easy to follow instructions.